



UT-V60S

Highlights:

- ✓ 20 SIP lines, SIP hotspot
- ✓ Embedded 1080P camera
- ✓ 112 one-touch DSS keys on 7" capacity color touch screen
- ✓ HD audio
- ✓ Support video codec H.264, for SIP video calls, RTSP video monitored. With Uniteli video door phone/intercom, you can make video preview and then open doors
- ✓ Dual Gigabit ports, integrated PoE
- ✓ desktop and wall mounted
- ✓ Compatible with major platforms: Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya etc.



As a high-end enterprise IP phone with Android 9.0 OS, Uniteli UT-V60S provides a more intelligent and smoother touch operation experience for the users. 112 DSS keys on the 7-inch color touch screen, supported 3rd party apps, built-in USB/TF interface allows unified communication smarter and simpler. Matching an adjustable embedded camera, Uniteli UT-V60S can deliver a superb audio and video for the group conference..

Generic

- 20 SIP Lines
- HD Voice
- HD video
- PoE Enabled
- 7-inch (1024x600) color touch screen
- Handset / Hands-free / Headset mode
- Intelligent DSS Keys(Virtual buttons)
- Optional External Power Supply

Operation System

- Android 9.0 OS with higher security and better compatibility
- Built-in Applications:
Files, Calendar, Gallery, Browser, Email, Calculator, Notepad, Sound Recorder, Clock, Video, Music
- Support 3rd Party Applications
- Secondary Development of API

Phone Features

- Local Phonebook (2000 entries)
- Remote Phonebook (XML/LDAP, 2000 entries)
- Intelligent Search for Contacts and Call Log
- Call logs (In/out/missed, 1000 entries)
- Black/White List Call Filter
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Action URL / Active URI
- Distinctive Ring
- Customized ring
- Audio/Video Recording
- SIP Hotspot
- Multicast
- Action Plan
- Time Plan

Maintenance & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP
- PNP/TR-069
- Web Management Portal
- Supports 3rd party communication APP
- Supports Web
- Supports encrypted configuration files download with AES
- Supports Web upgrade
- Supports factory reset data

Network

- Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4
- IP Configuration: Static / DHCP
- Network Access Control: 802.1x
- VPN: OpenVPN (Requires third-party app support)
- VLAN
- LLDP
- CDP
- QoS

Call Features

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (On server)
- 3-way Audio Conference
- Hot Line/Warm Line
- Direct IP call
- Hot desking
- BLF

Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.729AB, iLBC
- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO

Video

- Video decoding: H.264
- Video call resolution: QVGA/CIF/VGA/4CIF/720P/1080P
- Image format: JPEG/PNG/BMP
- Video format: MP4
- Bandwidth selection: 64kbps~4Mbps
- Frame rate selection: 5~30fps
- Video from remote site can be displayed in full screen
- Embedded Camera
- 2 Mega Pixel
- Flexible Placement and Angle Adjustment
- Video Preview

Protocols

- SIP2.0 over UDP/TCP/TLS
- DNS A/SRV/NAPTR
- RTP/RTCP/SRTP
- RTSP
- STUN
- DHCP
- CDP
- LLDP
- CDP
- 802.1x
- OpenVPN (Requires third-party app support)
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

Physical Specifications

- Color: Black
- LCD x1: 7 inches (1024x600) color touch screen,IPS
- Keypad: 5 keys, including
 - 1 home key
 - 1 return key
 - 1 hand free key
 - 2 Volume Control keys, Up/Down
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5 Ethernet Cable x1
- Back Rack x1
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- HDMI port x1: Type A
- USB2.0 Port x1: Standard A, Connect with Flash Driver
- TF card interface x1: 128G
- Power: 5V/2A or PoE Class3
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation: Desktop or Wall Mounted
- Device Dimensions
 - Desktop Stand(Angle 1): 254.8x154.9x202.8mm
 - Desktop Stand(Angle 2): 254.8x167.8x182.4mm
 - Wall Mounted: 254.8x118.4x206.9mm
- Gift Box Dimensions: 290x260x73mm
- Outer CTN Dimensions: 540x385x310mm (10 PCS)