



UNITELI

WiFi SIP Phone UT-W60

Top Features




WiFi



2 SIP Lines



HD Voice



132 * 58 Graphic Character Dot Matrix with Backlight
LCD



UT-W60 WiFi SIP Phone is a multi-access network, easy to deploy and operate desktop office phone for enterprise users, which features excellent sound quality, elegant and smart design. It supports 2 SIP accounts, which combines economical, practical and excellent performance dual advantage in one. It is an entry-level IP Phone specially designed for business office, suitable for enterprise

BASIC FUNCTIONS

132 * 58 graphic character dot matrix with backlight LCD
2 SIP accounts
Call Forward, Call Transfer, Call Waiting, Hotline, Call Hold, Auto Answer, Caller ID, Redial, Mute, DND
Local 3-Way Conferencing, Speed Dial, Voice Mail
Phone Book (1000)
Direct IP call without SIP proxy
Black list, white list
Dialed/received/missed call (each 200)
Call Center Headsets mode

PBX FEATURES

Intercom, Paging, Call pickup, Call park
Anonymous call, Anonymous call rejection
Hold on music, Conference Call, Group Listening, Group Pickup, DND&Call forward state synchronization
Call Recording

ADVANCED FEATURES

LDAP
Microsoft active directory server
XML remote phonebook

AUDIO FEATURES

8 own ring tone, 2 custom ring tone article
8 volume adjustable + Mute mode
Narrowband codec: G.711(A/μ), G.729A/B/AB, G.726, iLBC
Wideband codec: G.722, L16
Support VAD, CNG, AEC, PLC, AJB, AGC
Full-duplex speakerphone with AEC

NETWORK FEATURES

LAN / PC: support bridging mode
OpenVPN client support
SIP connection mode: Proxy mode, and P2P mode
Support DNS SRV (RFC3263)
NAT transverse: STUN mode
DTMF: In-band, RFC2833, SIP INFO
Support QoS
HTTP / HTTPS web server
Package tracing export
System log

WIFI FEATURES

Support IEEE 802.11b/g/n
Enhanced support for IEEE 802.11e QoS
Support APA, APA2, IEEE802.11i (WPA, WPA2)

SAFTY FEATURES

VLAN, LLDP, IEEE802.1X
Support TLS
Support HTTPS
SRTP (RFC3711)
Digest authentication using MD5/MD5
AES encryption for configuration file
Support phone lock, the administrator / user rating mode

CONFIGURATION

PnP configuration: based on the server implementation
• Manual configuration: Web, Keypad
• Batch deployment:
HTTP/FTP/TFTP/RPS/DHCP Option 66

PHYSICAL FEATURES

Power Interface: DC 5V-1A
2 RJ45 10/100M adaptive Ethernet ports
1 RJ9 headphone jack, 1 RJ9 handset jack
1 status indicator, 3 soft keys, 5 navigation keys
2 line keys, 2 volume keys
7 function keys (menu, cancel, voicemail, mute, headphone, Redial, handsfree)
Wall mountable
Operation Temperature: -10 ~ 50°C
Operating humidity: 10 ~ 90%

PACKAGE

Qty/CTN: 10 pieces
G.W/CTN: 11KG
Box Size: 280mm*210mm*78mm
Carton Meas: 425mm *415mm *300mm